

Article Print d Versio	late	EB 13.12.2018 2.3	Revisio	n date 29.09.2018		EN Page 1 / 7		
SEC	SECTION 1: Identification of the substance/mixture and of the company/undertaking							
1.1.	product identifiers							
		. (manufacturer/ ion of the substa		EB				
1.2.	. Relevant identified uses of the substance or mixture and uses advised against					ed against		
Relevant identified uses:								
				Print	ing aid			
1.3.	Details of	the supplier o	f the safety da					
	supplier ((manufacturer/i p & Co GmbH	-	nstream user/dist	ributor) hone: +49.61 9	98 30 40		
	Lorsbache D-65817 E	er Str. 28			ax: +49.61 98.3			
	Dept. res	ponsible for inf	ormation:					
	E-mail			info@	pruco-inks.com			
1.4.	-	cy telephone n	umber					
	Emergeno	cy telephone nur able during offic	nber	+49.6	61 98.30 40			
SEC	TION 2: H	azards identi	fication					
2.1.	Classifica	ation of the sub	stance or mi	xture				
	Classifica	Classification according to Regulation (EC) No 1272/2008 [CLP]						
	The mixtu	re is classified a	is hazardous a	according to regula	tion (EC) No 12	272/2008 [CLP].		
	Flam. Liq. STOT SE			ble liquids target organ toxic	ty (single	Flammable liquid and vapour. May cause respiratory irritation.		
	STOT SE	3 / H336	Specific exposur	target organ toxic e)		May cause drowsiness or dizziness.		
	•	hronic 2 / H411	Hazardo	ous to the aquatic e	environment	Toxic to aquatic life with long lasting effects.		
2.2.	Label ele							
			Regulation (E	C) No. 1272/2008	[CLP]			
		ictograms	¥2	Warning				
	Hazard st H226 H335 H336 H411	Ma Ma	y cause drows	and vapour. atory irritation. iness or dizziness ife with long lasting				
	Precautic P210 P370 + P3 P403 + P2	378 In d	ep away from case of fire, us		ing powder or a	ames and other ignition sources. No smoking. Icohol resistant foam. htly closed.		
	contains							
	0	-	drocarbons, CS					
	Supplemental Hazard information (EU) EUH066 Repeated exposure may cause skin d				dryness or cra	cking		
2.3.	EUH066 Repeated exposure may cause skin dryness or cracking. Other hazards							
	SECTION 3: Composition / information on ingredients							
		omposition /	mormation	on ingredients				
30	Mixtures							

3.2. Mixtures

RUCO

e No.: date on	EB 13.12.2018 2.3	Revision date 29.09.2018	EN Page 2 / 7	
Product of	description / che	emical characterization		
Descripti	on Solv	vent containing resin solution		
Hazardou	is ingredients			
Classifica	ation according	to Regulation (EC) No 1272/2008 [CLP]	1	
EC No. CAS No. INDEX No	Che	ACH No. emical name ssification: // Remark		Wt %
918-668-5 64742-95-	-6 hyd Flar	2119455851-35-XXXX rocarbons, C9, aromatics n. Liq. 3 H226 / STOT SE 3 H335 / . 1 H304 / STOT SE 3 H336	Aquatic Chronic 2 H411 / Asp.	50 - 100
203-933-3 112-07-2 607-038-0	2-bi	2119475112-47-XXXX utoxyethyl acetate te Tox. 4 H332 / Acute Tox. 4 H312		15 - 20
200-661-7 67-63-0 603-117-0	pro	2119457558-25-XXXX ɔan-2-ol n. Liq. 2 H225 / Eye Irrit. 2 H319 / STC	DT SE 3 H336	1 - 2,5

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures



Article No.:	EB		
Print date	13.12.2018		EN
Version	2.3	Revision date 29.09.2018	Page 3 / 7

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRBS 2153)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 35 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

2-butoxyethyl acetate INDEX No. 607-038-00-2 / EC No. 203-933-3 / CAS No. 112-07-2 WEL, TWA: 133 mg/m3; 20 ppm WEL, STEL: 332 mg/m3; 50 ppm Remark: (May be absorbed through the skin.) propan-2-ol INDEX No. 603-117-00-0 / EC No. 200-661-7 / CAS No. 67-63-0 TWA: 999 mg/m3; 400 ppm STEL: 1250 mg/m3; 500 ppm

Additional information

TWA : long-term occupational exposure limit value STEL : short-term occupational exposure limit value

Article No.:	EB		
Print date	13.12.2018		EN
Version	2.3	Revision date 29.09.2018	Page 4 / 7

Ceiling : peak limitation

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Occupational exposure controls

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

Hand protection

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance: Physical state: Colour:	Liquid refer to label
Odour:	characteristic
Odour threshold:	not determined
pH at 20 °C::	not applicable
Melting point/freezing point:	not determined
Initial boiling point and boiling range:	140 °C
Flash point:	47 °C
Evaporation rate:	not determined
Flammability (solid, gas): Burning time (s):	not applicable
Upper/lower flammability or explosive limits: Lower explosion limit: Upper explosion limit:	0,8 Vol-% 12 Vol-%
Vapour pressure at 20 °C::	48 mbar
Vapour density:	not determined
Relative density: Density at 20 °C::	0,98 g/cm³
Solubility(ies): Water solubility (g/L) at 20 °C::	insoluble
Partition coefficient: n-octanol/water:	see section 12
Ignition temperature in °C	375 °C
Decomposition temperature:	not applicable
Viscosity at 20 °C::	> 90 s 4 mm

RUCO

Article Print c Versic	date	EB 13.12.2018 2.3	Revision date 29	09.2018		EN Page 5 / 7	
				Method: DIN	153211		
	Explosive	properties:		not applical			
	Oxidising	-		not applical			
9.2.	Other infor	-					*
	Solid conte			30 Wt %			
	solvent cor						
	Organic s	olvents:		70 Wt %			
	Water:			0 Wt %			
0.00		paration test (%):		< 3 Wt % (A	UR/RID)		
SEC	TION 10: S	tability and reac	tivity				
10.1.	Reactivity Not applicat	ble.					
10.2.	Chemical s Stable when section 7.		mmended regulation	ons for storaç	ge and handling	. Further information on correct sl	torage: refer to
10.3.	-	of hazardous read from strong acids,		strong oxidizi	ng agents to ave	oid exothermic reactions.	
10.4.	Conditions Hazardous	to avoid decomposition byp	roducts may form	with exposure	e to high temper	atures.	
10.5.	Incompatik Not applicat	ble materials ble.					
10.6.	Hazardous Hazardous	decomposition p		with exposur	e to high tempe	eratures, e.g.: carbon dioxide, carl	bon monoxide,
SEC	TION 11: T	oxicological info	ormation				
		on according to Reg preparation itself a		272/2008 [CL	P]		
11.1.		n on toxicological					
	Acute toxic	-					
		al data are not avai	lable.				
	skin corros	sion/irritation; Ser	ious eye damage/	eye irritatior	1		
	Toxicologica	al data are not avai	lable.				
	Respirator	y or skin sensitisa	tion				
	Toxicologic	al data are not avai	lable.				
	Specific ta	rget organ toxicity	/				
	May cause :	respiratory irritatior	1.				
	May cause :	drowsiness or dizzi	ness.				
	Aspiration	hazard					
	-	al data are not avai	lable.				
		xperience/human					
	and respirat headache, o aforementio	solvent components tory organs, as wel dizziness, fatigue, a oned effects through	l as damage to the amyosthenia, drow n skin resorption. F	liver, kidneys siness, in ser Repeated or p	s and the centra ious cases: unc rolonged conta	hage, e.g. irritation of the mucous Il nerve system. Indications for this consciousness. Solvents may cause ct with the preparation may cause	s are: se some of the

aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Article No.: Print date	EB 13.12.2018	
Version	2.3	Revision date 29.09.2018

EN Page 6 / 7

SECTION 12: Ecological information

overall evaluation

Classification according to Regulation (EC) No 1272/2008 [CLP] There is no information available on the preparation itself . Do not allow to enter into surface water or drains.

12.1. Toxicity

Toxicological data are not available.

Long-term Ecotoxicity

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product

Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080312* waste ink containing dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

UN 1210

14.2.	UN proper shipping name Land transport (ADR/RID): Sea transport (IMDG): Air transport (ICAO-TI / IATA-DGR):	Printing ink PRINTING INK Printing ink
14.3.	Transport hazard class(es)	
		3
14.4.	Packing group	
		III
14.5.	Environmental hazards	
	Land transport (ADR/RID)	UMWELTGEFÄHRDEND
	Marine pollutant	p / AROMATIC HYDROCARBONS
14.6.	Special precautions for user	

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage. Advices on safe handling: see parts 6 - 8

Further information

RUCO

ticle No.:	EB							
rint date ersion	13.12.2018 2.3	Revision date 29.09.2018	EN Page 7 / 7					
Land trai	nsport (ADR/RID)							
tunnel res	striction code	D/E						
Sea trans	sport (IMDG)							
EmS-No.		F-E, S-D						
Air trans	port (ICAO-TI / IAT	TA-DGR)						
14.7. Transpo not applic		ig to Annex II of Marpol and the IBC Code						
SECTION 15:	Regulatory info	rmation						
15.1. Safety, h	ealth and environ	mental regulations/legislation specific for	the substance or mixture					
EU legis	EU legislation							
	Directive 2010/75/EU on industrial emissions VOC-value (in g/L): 686,436							
National	National regulations							
Observe	Restrictions of occupation Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).							
Other reg	gulations, restricti	ions and prohibition regulations						
	I Safety Assessme	ent ts for substances in this preparation were no	t carried out.					
SECTION 16:	Other information	on						
	of classification in							
	. 3 / H226	Flammable liquids	Flammable liquid and vapour.					
STOT SE	3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.					
	Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.					
Asp. Tox.		Aspiration hazard	May be fatal if swallowed and enters airways.					
STOT SE	3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.					
	x. 4 / H332	Acute toxicity (inhalative)	Harmful if inhaled.					
	x. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.					
	. 2 / H225	Flammable liquids	Highly flammable liquid and vapour.					
Eye Irrit.	2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.					
Remark								

n.a. =

= not applicable

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.

* Data changed compared with the previous version